

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number  
**WO 2005/069722 A2**

(51) International Patent Classification: Not classified

(21) International Application Number:  
PCT/GB2004/000204

(22) International Filing Date: 20 January 2004 (20.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: EAGLE, Timothy, Olof [GB/GB]; 10 Kings  
Avenue, Sudbury, Middlesex TW16 7QE (GB).

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

(74) Agents: WILLIAMS, Powell et al.; Morley House, 26-30  
Holborn Viaduct, London EC1A 2BP (GB).

Published:

— without international search report and to be republished  
upon receipt of that report

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: SHIM

(57) Abstract: A shim (10) for use in the building industry is formed of first and second wedge elements (12, 14) which are substantially parallel to one another and are of an elongate configuration. Each wedge element (12, 14) is provided with retaining means along one longitudinal side thereof, which take the form of a line of teeth (16, 18). These teeth (16, 18) have the purpose of holding between adjacent teeth a nail or screw which would keep the shim (10) in position. The two wedge elements (12, 14) are coupled together by a coupling element (40) at the thick end of the shim (10). The coupling between the element (40) and the wedge elements (12, 14) is such that the elements (12, 14) act in a unitary manner, substantially as would a shim formed by a single wedge element. The break lines (34, 36) at the top of the wedge elements (12, 14) enable the user to detach the wedge elements (12, 14) from the coupling element (40) so that they can be used separately. This can be useful when a shim of smaller dimensions is required.



WO 2005/069722 A2